

























MODELS













TRAILER

											
Code	Description	bar	l/h	°C	kW	kW	l	l	mm	kg	
1.128.360	JMB-S 200/18 T	200	1080	max. 110	11,7 (diesel)	70	50	200	2665x1559x1354	700	055
1.128.361	JMB-S+ 200/18 T	200	1080	max. 110	11,7 (diesel)	70	50	200	2665x1559x1354	705	055
1.128.510	JMB-S 250/15 T	250	900	max. 110	11,7 (diesel)	70	50	200	2665x1559x1354	700	040
1.128.511	JMB-S+ 250/15 T	250	900	max. 110	11,7 (diesel)	70	50	200	2665x1559x1354	705	040

BUILT-IN

											
Code	Description	bar	l/h	°C	kW	kW	l	l	mm	kg	
1.128.350	JMB-S 200/18 I	200	1080	max. 110	11,7 (diesel)	70	50		1575x920x865	450	055
1.128.351	JMB-S+ 200/18 I	200	1080	max. 110	11,7 (diesel)	70	50		1575x920x865	450	055
1.128.500	JMB-S 250/15 I	250	900	max. 110	11,7 (diesel)	70	50		1575x920x865	450	040
1.128.501	JMB-S+ 250/15 I	250	900	max. 110	11,7 (diesel)	70	50		1575x920x865	450	040

SKID

											
Code	Description	bar	l/h	°C	kW	KW	l	l	mm	kg	
1.128.355	JMB-S 200/18 S	200	1080	max. 110	11,7 (diesel)	70	50	200	1927x1198x1095	630	055
1.128.356	JMB-S+ 200/18 S	200	1080	max. 110	11,7 (diesel)	70	50	200	1927x1198x1095	630	055
1.128.505	JMB-S 250/15 S	250	900	max. 110	11,7 (diesel)	70	50	200	1927x1198x1095	630	040
1.128.506	JMB-S+ 200/15 S	250	900	max. 110	11,7 (diesel)	10	50	200	1927x1198x1095	630	040