

MODELS

										
Code	Description	bar	l/h	°C	kW	kW	l	l	mm	kg
1.134.D.354	JMB-MD 200/18 TG AK	200	1080	max. 110	11,5	110	80	450	3500 x 1800 x 1750	975
1.134.D.360	JMB-MD 200/18 TG AK SF	200	1080	max. 110	11,5	110	80	450	3500 x 1800 x 1750	985
1.134.D.454	JMB-MD 200/30 TG AK	200	1800	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1080
1.134.D.460	JMB-MD 200/30 TG AK SF	200	1800	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1090
1.134.D.466	JMB-MD 200/30 TG AK M2	200	1800	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1085
1.134.D.472	JMB-MD 200/30 TG AK SF2 M2	200	1800	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1095
1.134.D.544	JMB-MD 249/25 TG AK	249	1500	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1115
1.134.D.550	JMB-MD 249/25 TG AK SF	249	1500	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1125
1.134.D.556	JMB-MD 249/25 TG AK M2	249	1500	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1120
1.134.D.562	JMB-MD 249/25 TG AK SF2 M2	249	1500	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1130
1.134.D.604	JMB-MD-V 320/43 TG AK	320	2580	max. 110	31,5	110	80	450	3500 x 1800 x 1750	-
1.134.D.616	JMB-MD-V 320/43 TG AK M2	320	2580	max. 110	31,5	110	80	450	3500 x 1800 x 1750	-
1.134.D.654	JMB-MD 350/18 TG AK	350	1080	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1080
1.134.D.660	JMB-MD 350/18 TG AK SF	350	1080	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1090
1.134.D.829	JMB-MD 500/15 TG AK	500	900	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1160
1.134.D.835	JMB-MD 500/15 TG AK SF	500	900	max. 110	18,5	110	80	450	3500 x 1800 x 1750	1180
1.134.D.884	JMB-MD-V 500/30 TG AK	500	1800	max. 110	31,5	110	80	450	3500 x 1800 x 1750	1425

OPTIONAL EQUIPMENT

Code	Item description
1.234.290	(TP) Supplement for transfer pump
1.234.247	(DH) Supplement for pressure-retaining valve (to replace the standard pressure-free)
1.234.240	Supplement for light package JMB-MD/MG/ME: work light + beacon activatable with joystick
1.234.151	(TT) Supplement for track & trace system JMB-M 4G
1.890.000	Yearly subscription for the activation of the Track & Trace option.
1.234.399	(+) Supplement for plus-version: - Electronic level indication for fuel and water tank - Electronic gas control with automatic idling speed
1.234.07x	(COL) Supplement for protective housing in a DiBO RAL colour: (WH) RAL9016 - white (BK) RAL 9017 - black (BU) RAL 5002 - blue (OG) RAL 2009 - orange (Note: when ordering, please specify one of the following RAL colours)
1.234.074.(RAL)xxxx	(COL) Supplement for protective housing in your chosen RAL colour (Note: when ordering, please specify your chosen RAL colour)

OPTIONAL ACCESSORIES

Code	Item description
1.230.18x	Steam lance (Please always indicate when ordering the working pressure of the HP-cleaner)